Assign contact images with Symbian AIW

Overview

This code snipped shows how to assign images to contacts using the AIW handler.

This snippet can be self-signed.

Preconditions

Note: :This API is not part of the public SDK. It can be found in the SDK API Plug-in.

MMP file

The following library is required:

LIBRARY servicehandler.lib

In the resource file

Add the following headers:

```
#include <AiwCommon.hrh>
#include <AiwCommon.rh>
```

Then define a submenu item as follows in the MENU_PANE resource:

```
MENU_ITEM
 {
  command=EAssignSub;
  cascade=r_Assign_menu;
  txt = "Assign";
 }
```

Then define the actual submenu item as follows:

```
RESOURCE MENU_PANE r_Assign_menu
 {
  items =
   {
 MENU_ITEM
           {
            command=EAIWPlaceHolder2;
            txt = "";
            }
    };
  }
```

After which you can define the AIW menu interest item as follows:

```
RESOURCE AIW_INTEREST r_aiwmenutst_ASSIGN
 {
  items =
   {
    AIW_CRITERIA_ITEM
     {
       id = EAIWPlaceHolder2;
       serviceCmd = KAiwCmdAssign;
       contentType = "*";
       serviceClass = KAiwClassMenu;
     }
   };
}
```

Source file

Add the following header:

```
#include <AiwServiceHandler.h>
```


(C) Copyright Nokia 2013. All rights reserved.

Construct the CAiwServiceHandler and attach the menu:

```
iServiceHandler = CAiwServiceHandler::NewL();
iServiceHandler->AttachMenuL(R_ASSIGN_MENU, R_AIWMENUTST_ASSIGN);
```

Because the menu items for rotating were defined as submenus, you can handle adding the menu with the following code inside `DynInitMenuPaneL`:

```
if ( iServiceHandler->HandleSubmenuL( *aMenuPane ) )
 {
  return;
 }

if(iImageFileName.Length()
&& BaflUtils::Parse(iImageFileName) == KErrNone)
 {
        CAiwGenericParamList& paramList = iServiceHandler->InParamListL();

         TAiwVariant varFile(iImageFileName);
        TAiwGenericParam paramFile( EGenericParamFile, varFile );
        paramList.AppendL( paramFile );

        TAiwVariant varMime(_L("image/jpeg"));
        TAiwGenericParam paramMime( EGenericParamMIMEType, varMime );
        paramList.AppendL( paramMime );

         iServiceHandler->InitializeMenuPaneL(
         *aMenuPane,
         aResourceId,
         EAIWExampleCmdLast1,
         paramList);

}
else if(aResourceId == your Menu id goes here)
{
// Use aMenuPane->SetItemDimmed to dim out the menu item.
}
```

When the user selects the menu item, you just need to forward the command to `CAiwServiceHandler` in your command handler's default block as follows:

```
CAiwGenericParamList* paramList = CAiwGenericParamList::NewLC();

TAiwGenericParam filePath( EGenericParamFile, iImageFileName );
paramList->AppendL( filePath );

TAiwVariant varMime(_L("image/jpeg"));
TAiwGenericParam paramMime( EGenericParamMIMEType, varMime );
paramList->AppendL( paramMime );

iServiceHandler->ExecuteMenuCmdL(
 aCommand,
    *paramList,
 NULL,
 0,
 this);

CleanupStack::PopAndDestroy(paramList);
```


(C) Copyright Nokia 2013. All rights reserved.

(C) Copyright Nokia 2013. All rights reserved.