Bondi Widget porting example - standard Javascript

This article needs to be updated: If you found this article useful, please fix the problems below then delete the {{ArticleNeedsUpdate}} template from the article to remove this warning.

Reasons: hamishwillee
(28 Nov 2011)
The test widget package on which this depends is no longer available (/bondi.webvm.net/test.wgt). This needs to be relocated or the article needs to be updated to work off a new base widget.

Preface

This is an example of porting a Bondi Widget to Nokia WRT using the guide found here. The example widget does not use Bondi API functions, only standard Javascript. The widget demonstrates different methods of passing variables to another HTML-page.

1. Download the .wgt package

The Test widget wgt package can be found by following this link: bondi.webvm.net/test.wgt (link broken). This porting example was written using the Test widget version 1.1.

2. Rename and unzip the Test widget archive

The archive needs to be unzipped to make modifications to its contents. First rename the file extension from *.wgt to *.zip. Then extract the zip archive.

3. Create info.plist manifest file

When installing a .wgz file the system looks for a manifest file called info.plist. The Bondi Widget equivalent is called config.xml.

Here's how to use the Bondi Widget config.xml data to create the WRT manifest file:

1. Download and unzip this info.plist template file and save it in the widget's root directory.
2. Open the widget's config.xml file and find the `<name>` element. Copy the text found within the element and paste it into the `<string>` element under `<key>DisplayName</key>` element of the `info.plist` file.

```
<key>DisplayName</key>
<string>Test widget</string>
```

3. The identifier of a Bondi widget can be found in the `id` attribute of the `<widget>` element in `config.xml`. If the value is a URL, use the conventional WRT identifier form, which is the URL in reverse. Add the identifier to `<string>` element under `<key>Identifier</key>` element of the `info.plist` file.

```
<key>Identifier</key>
<string>net.webvm.bondi.test</string>
```

4. The HTML-file has not been specified in this Bondi widget. In this case, it searches for index.html by default.

```
<key>MainHTML</key>
<string>index.html</string>
```

5. This widget does not require network access so it can be set to false.

```
<key>AllowNetworkAccess</key>
<false />
```

6. Save the file.

4. Packaging

Re-zip the containing Test widget **folder** and change the file extension from *.zip to *.wgz.

5. Deploy

Upload the widget to your mobile device and install. Here is an example of the ported widget. Remember to change the extension to .wgz before installing.

(C) Copyright Nokia 2013. All rights reserved.

(C) Copyright Nokia 2013. All rights reserved.