# Twitter: Posting Tweets using Hammock

This article will help you in posting your tweets/ updating your timeline status in Twitter using Hammock library.. The screenshots of this project (assuming the user is logged in already) are shown below.

## Prerequisites

User should be already logged in Twitter to use the code shown in this article. You may refer this article to know about how to login to Twitter using Hammock.

## Code Snippet

The following method needs to be implemented to tweet posts in Twitter.

```
private void btnPostTweet_Click(object sender, RoutedEventArgs e)
        {
            var credentials = new OAuthCredentials
            {
                Type = OAuthType.ProtectedResource,
                SignatureMethod = OAuthSignatureMethod.HmacSha1,
                ParameterHandling = OAuthParameterHandling.HttpAuthorizationHeader,
                ConsumerKey = AppSettings.consumerKey,
                ConsumerSecret = AppSettings.consumerKeySecret,
                Token = this.accessToken,
                TokenSecret = this.accessTokenSecret,
                Version = "1.0"
            };

            var restClient = new RestClient
            {
                Authority = "http://api.twitter.com",
                HasElevatedPermissions = true
            };

            var restRequest = new RestRequest
            {
                Credentials = credentials,
                Path = "/1/statuses/update.json",
                Method = WebMethod.Post
            };

            restRequest.AddParameter("status", txtTweetContent.Text);
            restClient.BeginRequest(restRequest, new RestCallback(PostTweetRequestCallback));
        }
```

Using the above snippet, we've created an instance of *oAuthCredentials*, *RestClient* & *RestRequest* classes. All these classes are part of Hammock library. The *credentials* object is binded to the *RestRequest*'s object. The client request is fired and a callback is declared for catching the event.

- The callback event handler is defined as:

```
private void PostTweetRequestCallback(RestRequest request, RestResponse response, object obj)
        {
            Deployment.Current.Dispatcher.BeginInvoke(() =>
            {
                if (response.StatusCode == HttpStatusCode.OK)
                {
                    MessageBox.Show(AppSettings.TWEET_POSTED_SUCCESSFULLY);
                }
                else if (response.StatusCode == HttpStatusCode.Forbidden)
                {
                    MessageBox.Show(AppSettings.TWEET_POST_ERR_UPDATE_LIMIT);
                }
                else
                {
                    MessageBox.Show(AppSettings.TWEET_POST_ERR_FAILED);
                }
```


(C) Copyright Nokia 2013. All rights reserved.

```
                txtTweetContent.Text = "";
            });
        }
```

As shown in the above snippet, we are checking the response type and on it's basis, showing the proper prompt message to the user.

## Changes with Previous version

If you are following this article to get logged in in Twitter using Hammock and upgrading it with posting tweets code, then there are some changes in the UI.

## Changes in UI as compared to previous version of this article

- The mainPage.xaml file has the following contents now.

```
<Grid x:Name="ContentPanel" Grid.Row="1" Margin="12,0,12,0">
            <Grid.RowDefinitions>
                <RowDefinition Height="*"/>
            </Grid.RowDefinitions>

            <phone:WebBrowser Grid.Row="0" Margin="-6,3,0,1" Name="loginBrowserControl" Visibility="Collapsed"
                              Navigated="loginBrowserControl_Navigated" Navigating="loginBrowserControl_Navigating"
                              IsScriptEnabled="True"/>

            <Grid x:Name="TweetPanel" Grid.Row="0" Visibility="Collapsed">
                <Grid.RowDefinitions>
                    <RowDefinition Height=".15*"/>
                    <RowDefinition Height=".10*"/>
                    <RowDefinition Height=".60*"/>
                    <RowDefinition Height=".15*"/>
                </Grid.RowDefinitions>

                <TextBlock Grid.Row="0" x:Name="txtUserName" VerticalAlignment="Center" HorizontalAlignment="Center" FontSize="26" F
                <TextBlock Grid.Row="1" Margin="10" VerticalAlignment="Center" HorizontalAlignment="Left" Text="Enter your Tweet" Fo
                <TextBox Grid.Row="2" x:Name="txtTweetContent" Margin="20,-10,20,100" TextWrapping="Wrap" Text="" FontSize="24" Font
                <Button Grid.Row="3" x:Name="btnPostTweet" Content="Post Tweet" HorizontalAlignment="Center" Click="btnPostTweet_Cli

            </Grid>
        </Grid>
```

## Build and Run

- You may directly run the source code attached with this article to test it or embed the above defined methods in your own project.

## References

- http://nuget.org/
- http://nuget.org/packages/Hammock
- http://oauth.net/documentation/getting-started/
- https://dev.twitter.com/docs/auth/oauth


(C) Copyright Nokia 2013. All rights reserved.

(C) Copyright Nokia 2013. All rights reserved.